

FINAL RTV TUPE SILICONE

SECTION 1: IDENTIFICATIONS OF THE SUBSTANCE /MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product form : MIXTURE

Trade name : FINAL RTV SILICONE 30 GR

Product code : 5130 Sealant Acetoxy

Type of product : SILICONE SEALANT

Product group : TRADE PRODUCT

1.2. Relevant identified uses of the substance or mixture and uses discouraged

Intended use: Silicone sealant.

1.3. Details of the supplier providing the safety data sheet

Head office: Moscow, Kaluzhskoye highway, 1st kilometer, building 8B, business center "Slavyansky

Grad", 3rd floor.

Phone: +7 800 300 6200

contact@finalco.ru www.finalco.ru

1.4. Emergency telephone number

Poison emergency hotline Russia: +7 800 300 6200

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008:

Not a hazardous substance or mixture according to Regulation (EC) No. 1272/2008.

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008:

Not a hazardous substance or mixture according to Regulation (EC) No. 1272/2008.

Precautionary statements

P271 Use only outdoors or in a well-ventilated area.

Supplemental information

EUH210 Safety data sheet available on request.

EUH208 Contains: Bis[(2-ethyl-2,5-dimethylhexanoyl) oxy] (dimethyl) stannane. May

produce an allergic reaction.



EUH212 Warning! Hazardous respirable dust may be formed when used. Do not breathe

dust.

Endocrine disrupting properties

Environment: The substance/mixture does not contain components considered to have

endocrine

disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of

0.1% or higher.

Human Health: The substance/mixture does not contain components considered to have

endocrine

disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of

0.1% or higher.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature: Silicone elastomer.

3.1. Mixtures

This product is a mixture.

CASRN / EC-No. / Index- No.	REACH Registration Number	Concentration	Component	Classification: REGULATION (EC) No 1272/2008
CASRN 13463-67-7 EC-No. 236-675-5 Index-No. –	01-2119489379-17	<= 1.89 %	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	Carc. 2; H351 Acute toxicity estimate Acute oral toxicity: > 10,000 mg/kg Acute inhalation toxicity: > 6.82 mg/l, 4 Hour, dust/mist Acute dermal toxicity:
CASRN 556-67-2 EC-No. 209-136-7 Index-No. 014- 018-00-1	Ginal.	>= 0.2 - <= 0.29 %	octamethylcyclotetr asiloxane	Flam. Liq. 3; H226 Repr. 2; H361f Aquatic Chronic 1; H410 M-Factor (Chronic aquatic



Ginal Comments	File	CIA CIA	inal.	toxicity): 10 Acute toxicities estimate Acute oral toxicity: > 4,800 mg/kg Acute inhalation toxicity: 36 mg/l, 4 Hour,
Find		CE I CEMPATRICE	-mal	dust/mist Acute dermal toxicity: > 2,400 mg/kg
CASRN 68928-76-7 EC-No. 273-028-6 Index-No.	01-2120770324-57	>= 0.01 - <= 0.02 %	Bis [(2-ethyl-2,5-dimethyl hexanoyl) o xy] (dimethyl) stannane	Acute Tox. 4; H302 Skin Irrit. 2; H315 Skin Sens. 1A; H317 Aquatic Chronic 3; H412 Acute toxicity estimate Acute oral toxicity: 892 mg/kg Acute dermal toxicity: > 2,000 mg/kg

PBT and vPvB substance

CASRN 540-97-6 EC-No.	-0	>= 0.36 - <= 0.43 %	D <mark>odeca</mark> methyl	Not classified
208-762-8 Index-No.		THE REAL PROPERTY.	cyclohexasiloxane	Acute toxicity
				estimate Acute
				oral toxicity: >
				2,000 mg/kg
ACTIVITY & LEADING		CHICA CA		Acute dermal
		ADMINISTRA D OCALORS		toxicity: >
				2,000 mg/kg
CASRN 541-02-6 EC-No.	CHANGE & STATE OF	>= 0.2 - <= 0.31 %	Decam <mark>ethy</mark> lcy <mark>clo</mark> pe	Not classified
208-764-9 Index-No.		0.000	ntasi <mark>loxane</mark>	Acute toxicity
The state of the s			and the second	estimate Acute
0		The Paris of the P		oral toxicity: >
			9	24,134 mg/kg
-encl.				Acute
MARKET IN COLUMN TWO IS NOT THE OWNER.		TE ! THE	100	inhalation
676			CAL DIVISION	toxicity: 8.67
_ 0				mg/l, 4 Hour,
			.0	dust/mist
				Acute dermal
ACCOUNTS IN COLUMN 2 OF THE PARTY OF THE PAR				toxicity: >
		No. of Contrast	A SECULATION OF THE PERSON OF	2,000 mg/kg



Substances with a workplace exposure limit

CASRN 1328-53-6 EC-No.	01-2119459333-39	<= 1.22 %	C.I. Pigment Green7	Not classified
2 <mark>15-52</mark> 4-7 Index-No.			NAME OF TAXABLE PARTY.	Acute toxicity
				estimate Acute
		WELLOW, ANGELS	0	oral toxicity: >
				5,000 mg/kg
CASRN 20344-49-4 EC-No.	-	<= 1.08 %	Iron hydroxide	Not classified
243-746-4 Index-No.			oxide	Acute toxicity
				estimate Acute
	process of the same of the sam	CE P SAW WITH		oral toxicity: >
	27.0	. (()		10,000 <mark>m</mark> g/kg
album moral S. S.				

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General advice:

First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection).

Inhalation: Move person to fresh air and keep comfortable for breathing. If not breathing, give artificial respiration; if by mouth-to-mouth use rescuer protection (pocket mask, etc.) If breathing is difficult, oxygen should be administered by qualified personnel. Call a physician or transport to a medical facility.

Skin contact: Remove material from skin immediately by washing with soap and plenty of water. Remove contaminated clothing and shoes while washing. Seek medical attention if irritation or rash occurs. Wash clothing before reuse. Discard items which cannot be decontaminated, including leather articles such as shoes, belts and watchbands.

Eye contact: Flush eyes thoroughly with water for several minutes. Remove contact lenses after the initial 1-2 minutes and continue flushing for several additional minutes. If effects occur, consult a physician, preferably an ophthalmologist.

Ingestion: Rinse mouth with water. No emergency medical treatment necessary.

4.2 Indication of any immediate medical attention and special treatment needed Notes to physician: Maintain adequate ventilation and oxygenation of the patient. No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

SECTION 5: FIREFIGHTING MEASURES

Final ADHERIVES & SEALANTS

MATERIAL SAFETY DATA SHEET

5.1. Extinguishing media

Suitable extinguishing media: Water spray. Alcohol-resistant foam. Carbon dioxide (CO2). Dry chemical.

Unsuitable extinguishing media: None known.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products: Carbon oxides. Silicon oxides. Metal oxides. Cobalt compounds. Nitrogen oxides (NOx). Chlorine compounds.

Unusual Fire and Explosion Hazards: Exposure to combustion products may be a hazard to health.

5.3. Advice for firefighters

Fire Fighting Procedures: Use water spray to cool unopened containers. Evacuate area. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Remove undamaged containers from fire area if it is safe to do so.

Special protective equipment for firefighters: In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.

SECTION 6: HANDLING AND STORAGE

- **6.1. Precautions for safe handling**: Avoid contact with eyes. Do not swallow. Avoid prolonged or repeated contact with skin. Take care to prevent spills, waste and minimize release to the environment. Handle in accordance with good industrial hygiene and safety practice. CONTAINERS MAY BE HAZARDOUS WHEN EMPTY.
- **6.2. Conditions for safe storage, including any incompatibilities**: Keep in properly labelled containers. Store locked up. Store in accordance with the particular national regulations. Do not store with the following product types: Strong oxidizing agents. Unsuitable materials for containers: None known.

SECTION 7: EXPOSURE CONTROLS/PERSONAL PROTECTION

7.1. Control parameters

If exposure limits exist, they are listed below. If no exposure limits are displayed, then no values are applicable.

Component	Regulation	Type of listing	Value
octamethylcyclotetrasiloxane	US WEEL	TWA	10 ppm
Bis [(2-ethyl-2,5- dimethyl	ACGIH	TWA	0.1 mg/m3, Tin
hexanoyl)oxy](dimethyl)stannane			



Ginal.	Further information: A4: Not classifiable as a human carcinogen; Skin: Danger of cutaneous absorption		
ADMINIST PRIMARIA	ACGIH	STEL	0.2 mg/m3, Tin
	Further information: A4: N Danger of cutaneous abso	Not classifiable as a human prption	carcinogen; Skin:
Fill was seen and	GB EH40	TWA	0.1 mg/m3, Tin
	Further information: Sk: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.		
The state of the s	GB EH40	STEL	0.2 mg/m3, Tin
		Can be absorbed through the hose for which there are conditional to systemic toxicity.	
Decamethylcyclopentasiloxa ne	US WEEL	TWA	10 ppm
C.I. Pigment Green 7	GB EH40	TWA Dusts and mists	1 mg/m3, Copper
· Cenal	GB EH40	STEL Dusts and mists	2 mg/m3, Copper
Iron hydroxide oxide	GB EH40	TWA Fumes	5 mg/m3, Iron
	GB EH40	STEL Fumes	10 mg/m3, Iron
	GB EH40	TWA	1 mg/m3, Iron
The same of the sa	GB EH40	STEL	2 mg/m3, Iron

Although some of the components of this product may have exposure guidelines, no exposure would be expected under normal handling conditions due to the physical state of the material.

Predicted No Effect Concentration

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter \leq 10 μ m]

Compartment	PNEC
Fresh water	0.184 mg/l
Marine water	0.0184 mg/l
Intermittent use/release	0.193 mg/l
Sewage treatment plant	100 mg/l
Fresh water sediment	1000 mg/kg
Marine sediment	100 mg/kg
Soil	100 mg/kg

Octamethylcyclotetrasiloxane

Compartment	PNEC
Fresh water	0.0015 mg/l
Marine water	0.00015 mg/l
Fresh water sediment	3 mg/kg



Marine sediment	0.3 mg/kg
Soil	0.54 mg/kg
Sewage treatment plant	10 mg/l
Oral	41 mg/kg food

Dodecamethyl cyclohexasiloxane

Compartment	PNEC
Fresh water sediment	2.826 mg/kg
Marine sediment	0.2 <mark>82 mg/kg</mark>
Soil	3.336 mg/kg
Sewage treatment plant	> 1.0 mg/l

Decamethylcyclopentasiloxane

Compartment	PNEC
Fresh water	> 0.0012 mg/l
Marine water	> 0.00012 mg/l
Fresh water sediment	2.4 mg/kg
Marine sediment	0.24 mg/kg
Soil	1.1 mg/kg
Sewage treatment plant	> 10 mg/l

C.I. Pigment Green 7

Compartment	PNEC	
Fresh water sediment	10 mg/kg	
Marine sediment	1 mg/kg	
Soil	1 mg/kg	

SECTION 8: PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Physical state paste

Color black-grey

Odor acetic acid

Flash point closed cup >100 °C

Relative Density 1.02- 1.07 g/cm³

(water = 1)

Solubility(ies)

SECTION 9: STABILITY AND REACTIVITY

- **9.1. Reactivity**: Not classified as a reactivity hazard.
- 9.2. Chemical stability: Stable under normal conditions.
- **9.3. Possibility of hazardous reactions**: Can react with strong oxidizing agents.



- 9.4. Conditions to avoid: None known.
- **9.5. Incompatible materials**: Avoid contact with oxidizing materials.
- **9.6. Hazardous decomposition products**: Decomposition products can include and are not limited to: Formaldehyde.

SECTION 10: TOXICOLOGICAL INFORMATION

10.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Eye contact, Skin contact, Ingestion.

Acute toxicity (represents short term exposures with immediate effects - no chronic/delayed effects known unless otherwise noted)

Acute oral toxicity

Very low toxicity if swallowed. Harmful effects not anticipated from swallowing small amounts.

As product: Single dose oral LD50 has not been determined.

Based on information for component(s): LD50, Rat, > 5,000 mg/kg Estimated.

Information for components:

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

LD50, Rat, > 10,000 mg/kg.

Octamethylcyclotetrasiloxane

LD50, Rat, male, > 4,800 mg/kg No deaths occurred at this concentration.

Bis[(2-ethyl-2,5-dimethylhexanoyl) oxy] (dimethyl)stannane

LD50, Rat, male and female, 892 mg/kg OECD 401 or equivalent.

Dodecamethyl cyclohexasiloxane

LD50, Rat, male and female, > 2,000 mg/kg No deaths occurred at this concentration.

Decamethylcyclopentasiloxane

LD50, Rat, male and female, > 24,134 mg/kg.

C.I. Pigment Green 7

LD50, Rat, male and female, > 5,000 mg/kg OECD Test Guideline 401.

Iron hydroxide oxide

LD50, Rat, > 10,000 mg/kg.

Acute dermal toxicity

Prolonged skin contact is unlikely to result in absorption of harmful amounts.



As product: The dermal LD50 has not been determined.

Based on information for component(s): LD50, Rabbit, > 2,000 mg/kg Estimated.

Information for components:

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

LD50, Rabbit, 10,000 mg/kg.

Octamethylcyclotetrasiloxane

LD50, Rat, male and female, > 2,400 mg/kg No deaths occurred at this concentration.

Bis[(2-ethyl-2,5-dimethylhexanoyl) oxy] (dimethyl)stannane LD50, Rat, > 2,000 mg/kg.

Dodecamethyl cyclohexasiloxane

LD50, Rabbit, male and female, > 2,000 mg/kg.

Decamethylcyclopentasiloxane

LD50, Rabbit, male and female, > 2,000 mg/kg No deaths occurred at this concentration.

C.I. Pigment Green 7

The dermal LD50 has not been determined.

Iron hydroxide oxide

The dermal LD50 has not been determined.

Acute inhalation toxicity

Brief exposure (minutes) is not likely to cause adverse effects. Vapor from heated material may cause respiratory irritation.

Skin corrosion/irritation

Based on information for component(s): Prolonged exposure not likely to cause significant skin irritation. May cause more severe response if skin is abraded (scratched or cut). May cause more severe response on covered skin (under clothing, gloves).

SECTION 11: ECOLOGICAL INFORMATION

12.1 Toxicity

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

Acute toxicity to fish

Final

MATERIAL SAFETY DATA SHEET

Material is not classified as dangerous to aquatic organisms (LC50/EC50/IC50/LL50/EL50 greater than 100 mg/L in most sensitive species). NOEC mortality, Leuciscus idus (Golden orfe), static test, 48 Hour, > 1,000 mg/l

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), static test, 48 Hour, > 1,000 mg/l Acute toxicity to algae/aquatic plants EC50, Pseudokirchneriella subcapitata (green algae), 72 Hour, > 100 mg/l, OECD Test Guideline

Toxicity to bacteria

EC50, 3 Hour, > 1,000 mg/l, OECD Test Guideline 209
Octamethylcyclotetrasiloxane

Acute toxicity to fish

Based on testing of comparable products: The estimated maximum aqueous concentration of Octamethyl Cyclotetrasiloxane (D4) from migration to water from the product as supplied is below the D4 established no-effect threshold (< 0.0079 mg/L) for aquatic organisms.

Chronic toxicity to aquatic invertebrates

Based on testing for product(s) in this family of materials: Not classified due to data which are conclusive although insufficient for classification.

Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane

Acute toxicity to fish

Material is harmful to aquatic organisms (LC50/EC50/IC50 between 10 and 100 mg/L in the most sensitive species). For similar material(s): LC50, Zebra fish (Danio/Brachydanio rerio), semi-static test, 96 Hour, > 100 mg/l, OECD Test Guideline 203 or Equivalent

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna, static test, 48 Hour, 39 mg/l, OECD Test Guideline 202 or Equivalent

Acute toxicity to algae/aquatic plants

ErC50, Algae (Scenedesmus subspicatus), Growth rate, 72 Hour, Growth rate, 7.6 mg/l, OECD Test Guideline 201 or Equivalent For similar material(s): NOEC, Algae (Scenedesmus subspicatus), Growth rate, 72 Hour, Growth rate, 1.1 mg/l, OECD Test Guideline 201 or Equivalent

Toxicity to bacteria

For similar material(s): EC50, Bacteria, 3 Hour, Respiration rates., 14 mg/l

Final®

MATERIAL SAFETY DATA SHEET

SECTION 12: ACCIDENTAL RELEASE

12.1 Personal precautions, protective equipment and emergency procedures:

Use personal protective equipment. Follow safe handling advice and personal protective equipment recommendations.

- **12.2 Environmental precautions:** Discharge into the environment must be avoided. Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.
- 12.3 Methods and materials for containment and cleaning up: Wipe up or scrape up and contain for salvage or disposal. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Do not dump into any sewers, on the ground, or into any body of water. This product, when being disposed of in its unused and uncontaminated state should be treated as a hazardous waste according to EC Directive 2008/98/EC. Any disposal practices must be in compliance with all national and provincial laws and any municipal or local by-laws governing hazardous waste. For used, contaminated and residual materials additional evaluations may be required. The definitive assignment of this material to the appropriate EWC group and thus its proper EWC code will depend on the use that is made of this material. Contact the authorized waste disposal services.

SECTION 14: TRANSPORT INFORMATION

Classification for ROAD and Rail transport (ADR/RID):

14.1 UN number or ID number Not applicable

14.2 UN proper shipping name Not regulated for transport

14.3 Transport hazard class(es) Not applicable

14.4 Packing group Not applicable

14.5 Environmental hazards Not considered environmentally hazardous based on available

data.



14.6 Special precautions for user No data available.

Classification for SEA transport (IMO-IMDG):

14.1 UN number or ID number Not applicable

14.2 UN proper shipping name Not regulated for transport

14.3 Transport hazard class(es) Not applicable

14.4 Packing group Not applicable

14.5 Environmental hazards Not considered as marine pollutant based on available data

14.6 Special precautions for user No data available.

14.7 Maritime transport in bulk according to IMO instruments

Consult IMO regulations before transporting ocean bulk

Classification for AIR transport (IATA/ICAO):

14.1 UN number or ID number Not applicable

14.2 UN proper shipping name Not regulated for transport

14.3 Transport hazard class(es) Not applicable

14.4 Packing group Not applicable

14.5 Environmental hazards Not applicable

14.6 Special precautions for user No data available.

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACh Regulation (EC) No 1907/2006

This product contains only components that have been either registered, are exempt from registration, are regarded as registered or are not subject to registration according to Regulation (EC)

Final ADHESIVES & SEALANTS

MATERIAL SAFETY DATA SHEET

No. 1907/2006 (REACH)., The aforementioned indications of the REACH registration status are provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. It is the buyer's/user's responsibility to ensure that his/her understanding of the regulatory status of this product is correct.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII)

Conditions of restriction for the following entries should be considered:

octamethylcyclotetrasiloxane (Number on list 70) Bis[(2-ethyl-2,5-

dimethylhexanoyl)oxy](dimethyl)stannane (Number on list 20) Decamethylcyclopentasiloxane

(Number on list 70)

The following substance/s contained in this product might be or is/are subject to authorization in accordance with REACH:

CAS-No.: 556-67-2 Name: octamethylcyclotetrasiloxane

Authorisation status: listed in the Candidate List of Substances of Very High Concern for

Authorisation Authorisation number: Not available

Sunset date: Not available

Exempted (Categories of) Uses: Not available

CAS-No.: 540-97-6 Name: Dodecamethyl cyclohexasiloxane

Authorisation status: listed in the Candidate List of Substances of Very High Concern for

Authorisation Authorisation number: Not available

Sunset date: Not available

Exempted (Categories of) Uses: Not available

CAS-No.: 541-02-6 Name: Decamethylcyclopentasiloxane

Authorisation status: listed in the Candidate List of Substances of Very High Concern for

Authorisation Authorisation number: Not available

Sunset date: Not available

Exempted (Categories of) Uses: Not available

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Listed in Regulation: Not applicable



15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this substance/mixture.

SECTION 16: OTHER INFORMATION

H226	Flammable liquid and vapor.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H351	Suspected of causing cancer if inhaled.
H361f	Suspected of damaging fertility.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) No 1272/2008

This product is not classified as dangerous according to EC criteria.